

# LAWNNAIRE® V with EST



TRUST RYAN®

With Easy Steer Technology, the Lawnaire V maneuvers around highly landscaped areas—quickly and efficiently. Designed to rotate independently while driving, innovative tine assemblies allow you to steer without removing the tines from the ground—opening up a whole new world of productivity.

**1. 3/4" (19MM) DIAMETER, STEEL CORING TINES**

Unlike everyone else, our hardened alloy steel coring tines stay in the ground when you turn—and are durable enough to keep you out on the turf and out of the shop.

**2. EASY STEER TECHNOLOGY**

Save your strength with Easy Steer Technology and easily maneuver along paths and contours—even 180° turns. Outer tines rotate faster during turns to maintain deep core penetration without tearing up turf, increasing your productivity without sacrificing quality.

**3. SIZED TO YOUR NEEDS**

Need to maximize your productivity? The Lawnaire V has you covered with a 26.5-in aeration width.



**SIMPLIFIED LIFTING AND TRANSPORTING**



**FRONT BUMPER GUARD**



**ADJUSTABLE WEIGHT DISTRIBUTION**



FOR MORE INFORMATION, VISIT [RYANTURF.COM](http://RYANTURF.COM)



FOR MORE INFORMATION,  
VISIT [RYANTURF.COM](https://www.ryanturf.com)

## LAWNAIRE® V SPECIFICATIONS

<b>HONDA® Engine Model</b>	4-cycle Honda® GX120; recoil start; on/off switch; low-oil alert
<b>HONDA Displacement</b>	7.2 cu in. (118 cc)
<b>HONDA Fuel Capacity</b>	0.53 gal (2 L)
<b>HONDA Oil Capacity</b>	0.59 qt (0.56 L)
<b>BRIGGS &amp; STRATTON® Engine Model</b>	4-cycle Vanguard™ 200 Model 12V3; recoil start; TransportGuard® integrated fuel valve/throttle; low-oil alert
<b>BRIGGS &amp; STRATTON Displacement</b>	9.9 cu in. (163 cc)
<b>BRIGGS &amp; STRATTON Fuel Capacity</b>	0.82 gal (3.1 L)
<b>BRIGGS &amp; STRATTON Oil Capacity</b>	0.61 qt (0.58 L)
<b>Clutch</b>	Belt tightener
<b>Drive: Primary</b>	4L section V-belt
<b>Drive: Tine &amp; Drum</b>	Single #40 nickel-plated chain
<b>Tines</b>	0.75 in. (19 mm) diameter coring-type formed from 0.08 in. (2 mm) hollow, hardened alloy steel
<b># of Tines</b>	42 tines per aerator
<b>Lubrication</b>	Grease fittings on the wheels, tine wheels, and idler pivot/oil chain
<b>Coring Depth</b>	Up to 2.75 in. (70 mm)
<b>Core Diameter</b>	0.75 in. (19 mm)
<b>Aeration Pattern</b>	3.75 in. x 7 in. (95 mm x 178 mm)
<b>Aerating Width</b>	26.5 in. (673 mm)
<b>Productivity</b>	Aerates up to 40,000 sq ft/hr (3,716 m <sup>2</sup> /hr) at 3.5 mph
<b>Tires</b>	(2) 8 x 2.25 semi-pneumatic with ball bearings
<b>Weight: Wet</b>	250 lb (113 kg)
<b>Weight: Wet w/ Weights</b>	290 lb (132 kg)
<b>Weight: Wet w/Weights &amp; Water in Drum</b>	344 lb (156 kg)
<b>Width</b>	35.5 in. (902 mm)
<b>Length</b>	53.5 in. (1,359 mm)
<b>Height</b>	48.5 in. (1,232 mm)

One Bobcat Lane | Johnson Creek, WI 53038-0469

For more information about RYAN® products, visit your RYAN® dealer today. For the location of the dealer nearest you, call 866-469-1242 or visit [www.ryanturf.com](https://www.ryanturf.com).

©2022 Clark Equipment Co. All Rights Reserved.



**TRUST RYAN®**